EB-E20

DATASHEET / BROCHURE



With the versatility to mount just about anywhere, bright, sharp images and low maintenance, the EB-E20 is a great all-rounder for business.

The EB-E20 offers a very versatile proposition that can be mounted just about anywhere. Meanwhile long lamp life and trusted Epson durability offer peace of mind and minimal maintenance.

Bright, vivid content on a large scalable screen

Enjoy large scale presentations with crisp, clear text, as well as compelling imagery and video content, on screen sizes up to 350 inches. 3,400-lumen performance combines with a high contrast ratio of 15,000:1 to offer outstanding visual performance, even in well-lit rooms.

Years of uninterrupted meetings

With a lamp life of up to 12,000 hours in Eco mode.

Easy to use

Built-in lens shutter that allows easy restart and shut down. User friendly home screen that enables you to confidently and easily connect your device to the projector.

Multiple inputs on one display with audio

Display size matters; scalable up to 350" to enhance your viewing experience and ensure that content shown is not too small. That way everyone in your meeting has the same opportunities to share and engage.

High quality sound

This projector has a built-in 5W speaker to allow audio content to be heard clearly without the need for separate external speakers.

KEY FEATURES

- High-quality bright images 3LCD technology and equally high White and Colour Light Output
- Portable

Small and light enough to be moved easily and used in multiple rooms

- High quality sound Built-in 5W speaker for crisp, clear sound
- Low total cost of ownership Lamp life up to 12,000 hours in Eco mode
- Versatile and flexible control Project from many sources with HDMI



PRODUCT SPECIFICATIONS

ECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
CD Panel	0.55 inch with C2 Fine
Color Light Output	3,400 Lumen- 2,200 Lumen (economy) In accordance with IDMS15.4
Vhite Light Output Resolution	3,400 Lumen - 2,200 Lumen (economy) In accordance with ISO 21118:2020 XGA
Aspect Ratio	4:3
Contrast Ratio	15,000 : 1
ight source	Lamp
amp	UHE, 210 W, 6,000 h durability, 12,000 h durability (economy mode)
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
Colour Video Processing	10 Bits
D Vertical Refresh Rate	100 Hz - 120 Hz
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
hrow Ratio	1.44 - 1.95:1
loom	Digital, Factor: 1 - 1.35
Screen Size	30 inches - 350 inches
Projection Distance Wide/Tel	e 1.76 m (60 inch screen
Projection Lens F Number	1.44
Projection Lens Focal Length	16.7 mm
Projection Lens Focus	Manual
Offset	8:1
CONNECTIVITY	
JSB Display Function	2 in 1: Image/ Sound
nterfaces	RS-232C, VGA in (2x), VGA out, HDMI in, Composite in, Jack plug out, Jack plug in (2x), Cinch
	audio out, USB 2.0
Epson iProjection App	Ad-Hoc / Infrastructure
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Security cable hole, Password protection
D Colour Modes	Dynamic, Cinema, Presentation, sRGB, Blackboard
Other features	AV Mute Slide, CEC compatible, Digital zoom, Direct Power on/off, Document Camera
Cala a O a la a Marala a	Compatible, OSD copy function, Quick Corner, Split-Screen-Function
/ideo Color Modes	Blackboard, Dynamic, Presentation, sRGB, Theatre
GENERAL	
ower consumption	286 Watt (Normal On-Mode), 180 Watt (Eco On-Mode), 327 Watt (Normal Peak-mode), 225
	Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	309 x 282 x 87 mm (Width x Depth x Height)
Product weight	
loise Level	2.7 kg
	2.7 kg Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	-
	Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C
Supported Temperature Supported Humidity	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
Supported Temperature Supported Humidity	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case,
Supported Temperature Supported Humidity Options	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01
Supported Temperature Supported Humidity Options .oudspeaker	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt
Supported Temperature Supported Humidity Options Soudspeaker Room Type / Application	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt Boardroom, Huddle space / Portable, Meeting room / Classroom
Supported Temperature Supported Humidity Options Loudspeaker Room Type / Application Positioning Colour	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt Boardroom, Huddle space / Portable, Meeting room / Classroom Ceiling Mounted, Desktop
Supported Temperature Supported Humidity Options Loudspeaker Room Type / Application Positioning	Normal: 37 dB (A) - Economy: 28 dB (A) Operation 5° C - 40° C, Storage 10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Air filter, Ceiling mount, Document camera, External Speaker, Safety wire set, Soft carry case, Spare lamp, Suspension adapter, WP System - ELPWP20, Wireless transmitter - ELPWT01 5 Watt Boardroom, Huddle space / Portable, Meeting room / Classroom Ceiling Mounted, Desktop

EB-E20

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries

EPSON[®]

- Warranty card
- Quick Start Guide
- HDMI Cable 1.8m

OPTIONAL ACCESSORIES

- Soft Carry Case ELPKS70
- Lamp ELPLP97 EB9XX/W49/X/E20/U50/EB-x05/x41/x42/EH-TW6 V13H010L97
- Air Filter ELPAF32
- Ceiling Pipe (450mm) ELPFP13
- Ceiling Pipe (700mm) ELPFP14
- V12H467040
- V12H467040DA
- Ceiling Mount (White) ELPMB23 V12H003B23

LOGISTICS INFORMATION

SKU	V11H981040DA
EAN code	8715946686189
Country of Origin	Philippines

V12H001K70

- V13H134A32
- V12H003P13
- V12H003P14
- Safety Wire ELPWR01

Epson Middle East P.O.Box 17383, Dubai

- V12H003W01 • Active Speakers (2 x 15W) - ELPSP02
- Active Speakers (2 x 15W) ELPSP02

United Arab Emirates Telephone: +9714 8818934 Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

Hotline Telephone: +9714 8872172

Fax: +9714 8818945

www.epson.ae

EB-E20